



.110" Wall Thickness
 1.25" Pole Diameter
 2.6 Lbs Based On 6' Extension Pole

Preferred For Aerial Construction And Line Clearance

Jameson's original foam core pole is the highest quality fiberglass pole available.

Foam core prevents debris and moisture build up inside pole and adds extra hoop strength and rigidity.

High visibility color.

Protective surface veil prevents fibers blooming at surface due to abrasion or ultra-violet light.

Meets requirements of OSHA Subpart V 1926.951(d)(1)(i):

Every JE series pole is tested to 100KV per foot for 5 minutes.

Not a "hot stick."

- Attach Tool Head to Pole's Ferrule (Pruner or Pole Saw) with Adapter

- For Additional Length, Attach Extension Pole(s) Into Base Pole



Pole	Ferrules	6'	8'	10'	12'
Extension Pole	Female Ferrule & Male Ferrule	JE-6	JE-8	JE-10	JE-12
Base Pole	Rubber Base Cap & Female Ferrule	JE-6F	JE-8F	JE-10F	JE-12F
Sawhead Pole *	Male Ferrule & PS-3FP Sawhead Permanently Mounted on Pole	JE-6SFP	JE-8SFP	JE-10SFP	JE-12SFP



Sawhead Pole Permanent Mount with Saw Blade



Sawhead with Pole Adapter Snaps Into Base or Extension Pole's Ferrule

* Sawhead Pole has permanently mounted sawhead for attaching saw blade directly to pole.

Sawhead is available separately with adapter that snaps into female ferrule of Extension or Base Pole (see Pole Saws)

For highest performance and safety, Jameson recommends using a Base Pole when using one pole or starting with a Base Pole when working with multiple poles.