

# LASHING WIRE

## 61000, 61010, 61020, 61030, 61040 SERIES

The difference between this lashing wire and other lashing wires isn't visible to the eye. While all lashing wires may look and feel alike, our lashing wire is specially annealed for extra durability where the lash meets the strand.

Wound in continuous coils for easy payout, our lashing wires won't come back to haunt you. Instead, the lash holds tight and stays even. We give you 14 choices of size and types: Aluminum, galvanized, various grades of stainless and non-metallic. All come in popular sizes to match any job, and while our sizes and types vary, our quality doesn't.



**STRAIGHT HUB:** Industry standard coils (5-1/2") to fit the Lineman and Eagle Lashers, and other lashers with drop-down doors.

**TAPERED HUB:** Standard outside diameter to fit a tapered Cable Spinning Equipment hub (eg, D lashers).

**DISPOSABLE METAL REELS:** Pre-coiled on 6" aluminum reels, to fit legacy CSE lashers with a 1-1/4" mounting post. (CSE K & Special K lashers).

**Q-SIZED:** Compact coils (4" diameter) to fit the Model Q Lasher.

**NON-METALLIC MATERIAL:** Two sizes, one for industry-standard straight hub lashers like the Lineman; a second, high-capacity spool to fit our modified lashers. Note: a lasher tension adjustment mechanism is necessary to compensate for the softer aramid strand.

### LASHING WIRE SPECIFICATIONS

| Lasher                            | Part No.  | Model      | Wire Dia. | Material      | Coils/Box | Length   | Net Box Weight | Total Coil Weight |
|-----------------------------------|-----------|------------|-----------|---------------|-----------|----------|----------------|-------------------|
| <b>Straight Hub</b>               |           |            |           |               |           |          |                |                   |
| Lineman, Eagle, S, K, & Special K | 61010-020 | 10A-3A     | 0.061"    | 316 STAINLESS | 6         | 650 FT   | 42 LB          | 7.00 LB           |
|                                   | 61010-040 | 12A-3A     | 0.091"    | GALVANIZED    | 6         | 325 FT   | 45 LB          | 7.19 LB           |
|                                   | 61010-050 | 13A-3A     | 0.045"    | 430 STAINLESS | 6         | 1,200 FT | 41 LB          | 6.56 LB           |
|                                   | 61010-070 | 26A-3A     | 0.045"    | 316 STAINLESS | 6         | 1,200 FT | 42 LB          | 6.69 LB           |
|                                   | 61010-080 | 27A-3A     | 0.045"    | 302 STAINLESS | 6         | 1,200 FT | 42 LB          | 6.69 LB           |
| <b>Tapered Hub</b>                |           |            |           |               |           |          |                |                   |
|                                   | 61000-050 | 13A-1A     | 0.045"    | 430 STAINLESS | 6         | 1,200 FT | 41 LB          | 6.56 LB           |
| <b>Disposable Metal Reels</b>     |           |            |           |               |           |          |                |                   |
| Legacy K & Special K              | 61020-010 | 7AK-1AK    | 0.091"    | ALUMINUM      | 5         | 350 FT   | 19 LB          | 3.31 LB           |
|                                   | 61020-020 | 10AK-1AK   | 0.061"    | 316 STAINLESS | 5         | 750 FT   | 43 LB          | 8.34 LB           |
|                                   | 61020-030 | 11AK-1AK   | 0.061"    | 430 STAINLESS | 5         | 750 FT   | 42 LB          | 8.19 LB           |
|                                   | 61020-050 | 13AK-1AK   | 0.045"    | 430 STAINLESS | 5         | 1,400 FT | 43 LB          | 8.31 LB           |
|                                   | 61020-060 | 23ANM-1AK  | N/A       | NON-METALLIC  | 5         | 1,200 FT | 11 LB          | 1.87 LB           |
| <b>Special</b>                    |           |            |           |               |           |          |                |                   |
| Q                                 | 61030-010 | 10AS-1AS   | 0.061"    | 316 STAINLESS | 8         | 225 FT   | 20 LB          | 2.30 LB           |
|                                   | 61030-020 | 11AS-1AS   | 0.061"    | 430 STAINLESS | 8         | 225 FT   | 20 LB          | 2.26 LB           |
|                                   | 61030-030 | 13AS-1AS   | 0.045"    | 430 STAINLESS | 8         | 375 FT   | 18 LB          | 2.05 LB           |
| <b>Non-Metallic Material</b>      |           |            |           |               |           |          |                |                   |
| Straight-Hub & Modified           | 61040-009 | -          | N/A       | NON-METALLIC  | 6         | 900 FT   | 8.4 LB         | 0.91 LB           |
|                                   | 61040-010 | 23ANM-3A   | N/A       | NON-METALLIC  | 6         | 1,000 FT | 9 LB           | 1.01 LB           |
|                                   | 61040-020 | 23ANM-4000 | N/A       | NON-METALLIC  | 1         | 4,000 FT | 5 LB           | 4.04 LB           |