

STANDARD

CORRUGATED

- Manufactured from flexible HDPE
- Rugged corrugated design is flexible and light weight, yet provides excellent crush resistance
- Outstanding long term cable protection from shifting ground, rock and root impingement
- Provides a permanent pathway, simplifies future cable repairs or replacement
- Factory pre-installed Bull-Line™ Pull Tape with EVEN-LOAD™, ensures extra slack at any access point throughout the reel. Available 500 lb–6,000 lb tensile strength or locatable. Comes standard on 2"; is available for 1"-1.5"



installation types

Existing Conduit
Indoor
Short Runs

sizes range

1.0" 1.5"
1.25" 2.0"

standard colors 1", 1¼", 1½"




custom colors available

standard colors 2"



FEATURES

STANDARDS FOR 1", 1¼", 1½"	STANDARDS FOR 2"
PUT-UPS Continuous lengths on reels or in coils	PUT-UPS Available in 250' coils only
FOOTAGE MARKINGS Sequential foot or meter markings; custom print streams available	SHIPS 3 coils per pallet
OPTIONS FOR 1", 1¼", 1½"	SINGLE WALL standard conduit
UV PROTECTANT for above ground applications	1250 LB PULL TAPE comes standard
PLENUM & RISER for behind the wall applications	



CORRUGATED TECHNICAL SPECIFICATIONS

NOMINAL SIZE	NOMINAL OD (IN)	ID REF (IN)	MIN WALL THICK (IN)	BRITTLENESS TEMP	BEND RADIUS* (IN)	WEIGHT (LB/FT)	SWPS† (LBS)
1"	1.385	1.220	0.045	-75°C	14	0.113	500
1.25"	1.570	1.440	0.045	-75°C	16	0.125	500
1.5"	1.824	1.670	0.055	-75°C	19	0.165	500
2"	2.490	2.045	0.020	-75°C	22	0.196	500

*Unsupported Bend Radius guidelines should be followed during the installation process. The Supported Bend Radius are post-installation measurements.
 †Safe working pull strength is calculated at 80% of tensile or breaking strength

2" CORRUGATED ORDERING INFO

NOMINAL SIZE	COLOR	PART NUMBER
2"	■	20003440
2"	■	20004740
2"	■	20004739
2"	■	20003441
2"	■	20004741