


SPECIALTY

UL FLEX DUCT

- Non-metallic, liquid-tight flexible conduit
- UL listed for sizes 1/2" – 4" (1660, Type B)
- Sunlight (UV) resistant
- Flexible PVC: eliminates the need for special preformed bends
- Excellent cable protection from ground line to meter/service box
- Used for cable protection and above and below ground installation applications
- UL listed for use in continuous temperatures from 105 C (221 F) Dry, 60 C (140 F) Wet, or 80 C (176 F) Dry, 60 C (140 F) Wet, 70 C (158 F) oil resistant or less
- Use fittings identified for Type B conduit or use fittings for liquid-tight flexible metal conduit. FNMC-B is directly marked on non-metallic fittings that are intended for integral conduit



INSTALLATION TYPES

Cable Protection
Above and Below
Ground Installation

SIZE RANGE

0.5" 1.5"
0.75" 2.0"
1.0" 4.0"
1.25"

STANDARD COLORS

■ Gray Coils, Empty

UL FLEX DUCT ORDER REFERENCE

SIZE	AVG OD (IN)	AVG ID (IN)	WEIGHT/COIL (LBS)	COIL LENGTH (FT)	PART NUMBER
1/2"	0.840	0.642	15	100	20001541
3/4"	1.050	0.840	22	100	20000409
1"	1.315	1.066	30	100	20000410
1 1/4"	1.660	1.410	20	50	20000411
1 1/2"	1.900	1.600	24	50	20000412
2"	2.375	2.045	32	50	20000413
4"	4.530	4.045	180	100	20005285